

## Nautilus P2.5 Dewinterization (Tab 320)

Your Valves will be in **Winterization** mode from the wintertime



Your Alde bypass should be in BYPASS MODE as well – keep it in this mode



Before starting, drain as much Antifreeze from your system as possible by opening low point drain valves and holding tanks (Fresh, Gray and Black)

### Steps

1. First fill a bucket with sanitation Fluid (1/2 Cup Bleach with 1 Gallon of water mixture)



a.

2. Put your Nautilus into **SANITATION** mode



a.

3. Hook up a hose to your Sanitation Connection from the bucket



a.

4. Turn on Pump and Fill your fresh-water tank with the Sanitation Fluid

5. Put your Nautilus into **DRY CAMPING** mode



a.

6. Turn on your Pump

7. Run the sanitation fluid through all your water faucets/fixtures

8. Place your Nautilus into **TANK-FILL** mode



a.

9. Hook up a city water connection and fill your fresh-water tank

10. Place your Nautilus into **DRY CAMPING** mode



a.

11. Turn on your pump and Run fresh water through all your faucets / fixtures

12. Once your tank is empty place the Nautilus back into **TANK-FILL** mode



a.

13. Hook up your city water connection again and fill the fresh-water tank with fresh water

14. Place your Nautilus back into **DRY CAMPING** mode



a.

15. Turn on your pump and run Fresh water through all the same water faucets / fixtures

16. You can then turn your Alde Valve back to NORMAL



a. 

17. Your unit should be sanitized and flushed – Congrats! You are ready to camp again!